

T-MAX™ 405

The first solution for interior
plasters and decorative materials



PROFESSIONAL ADVANTAGES

- Easier and faster than applying texture manually
- Lightweight and modular system
- Applies most plasters without compressor

MATERIALS

Interior plasters - Decorative materials



T-MAX™ 405

The first solution for interior
plasters and decorative materials

ACCESSORIES

Convertible Lance

248164 T-Max lance
convertible

Lance Filters

248522 18 mesh T-Lance filter
with cap and seal (x 2)
248521 30 mesh T-Lance filter
with cap and seal (x 2)

T-Material Hoses

248518 10 m x 1" (25 mm)
248519 5 m x 1" (25 mm)
248520 3 m x 3/4" (19 mm)
T whip hose

! Graco does not recommend exceeding a total length of 15 m. Use 3 sections of 5 m x 1" to achieve this length.

Air Hose

with air regulator and
QuikDisconnect™ connections

248557 Air Hose kit
15 m x 3/8"

Bag Roller

248517* T-Max bag
rolling kit

** with slide bars and mounting hardware.*

T-Max extension

248523 120 cm for air applica-
tions (ceilings)

Foam cleaning ball

248515 1" - kit (x2)

TMX Tips

Specifically designed for the applica-
tion of plasters and fillers

Xtra light	Light
TMX531	TMX541
TMX535	TMX545
Medium	Heavy
TMX651	TMX671
TMX661	-

Round Air Nozzles

248888 3 mm
248524 4 mm
248525 6 mm
248526 8 mm
248527 10 mm

• Do not use tip sizes with orifice smaller than 0.031"
• Some plasters and fillers may require 2% - 10% thinning to spray compressorless based on temperature, viscosity and mixing. Always spray a test pattern before use.



1

Quick to set up :
No tool connections
Ready to spray



2

Compressorless



3

with air

Offers the unique option to apply most plasters without a compressor = faster set-up time, less noise, less masking, cleaner application, easier, etc.



Portability

Big wheels to go over rough terrain

Pump and hopper are detachable without tools

Heavy duty frame with front and rear handles



Quick to clean

Steep walls Stainless Steel hopper
Drain plug
Detachable from frame

Performance

First compressorless sprayer
Supports up to 15 m hose
Sprays plaster 1 meter away from walls and ceilings



Reliability & life

Hard chromed piston and pump housing against wear
Extra large fluid passages
Spring loaded balls for trouble free operation



Easy to use

One button only
Green with air - blue without air
Quick pump access, no tools



T-MAX™ 405

SPECIFICATIONS

Part Numbers:

		T-Max™ 405
110 V for UK		249075
220 V for Europe complete		248195
220 V for Italy, Denmark, Switzerland		248269
Max. Working Pressure		40 bar
Max. Fluid Flow (depending on material density)		5.7 l/min (9.6 kg/min*)
Max. Fluid Flow with plaster		5.0 l/min (8 kg/min)
Motor		0.875 HP (0.65 Kw)
Max. Hose Length		15 m
Hopper Capacity		45 liter (2 bags)
Max. Particle Sizes	Compressorless	0.25 mm
	with Compressor	3.00 mm
Weight	T-Max complete	51 kg
	T-Max Sprayer only	20 kg
	Hopper	10 kg
	Cart	15 kg

T-Max 405 ships complete with hopper, cart and unit. 5 m x 1" hose + 3 m x 3/4" whip hose = 8 m.

T-Box contains lance, brush, 6 mm air nozzle, TMX651 tip, 2 filters, cup, hopper plug, pump boot, tip cleaning tool and measuring cup.

15 m x 3/8" air hose with air regulator.