

CABLE CUTTERS

KT



KT 1
Hand operated tool
for cutting cables
up to a maximum \varnothing 15 mm



KT 2
Hand operated tool
for cutting cables
up to a maximum \varnothing 25 mm



KT 5
Hand operated tool
for cutting cables
up to max section 25 sqmm

CABLE CUTTERS



5116660250
For cutting cables 6 to 250 sqmm
Weight: 1,5 kg
Length: 600 mm



5116660500
For cutting cables 6 to 500 sqmm
Weight: 3 kg
Length: 800 mm

CABLE CUTTERS



KT 3
For cutting cables \varnothing max 32 mm
Weight: 0,59 kg
Length: 255 mm



KT 4
For cutting cables \varnothing max 52 mm
Weight: 0,89 kg
Length: 310 mm

HAND TOOL FOR CUTTING AND SEALING FLEXIBLE CONDUIT

KTS 1632



Cuts and seals flexibles plastic conduit in a single operation. Lightweight and easy to operate. Suitable for flexible conduits from Ø16 to Ø32 mm.

Length: 230 mm
Width: 58 mm
Thickness: 32 mm.
Weight: 0,32 kg.

PC 1



Plastic pipe cutting tool
 Cutting capacity: Ø6 to Ø42 mm.

Body: die-cast aluminium alloy
 Blade material:
 hardened carbon steel

MECHANICAL HOLE PUNCHING TOOL FOR CABLE TRUNKING

MT-FC47

Table denotes the punch/die set reference, for each hole size.
 Suitable for punching holes in mild steel, fibreglass or plastic material, up to 3 mm thick.

Hole Dimensions					Maximum thickness of mild steel mm	Code
Ø mm	Ø inch	Pg	ISO	Tube		
15,2	.598	Pg 9	-	-	2	RD 15,2 S
16,2	.638	-	ISO-16	-		RD 16,2 S*
17,5	.688	-	-	-		RD 17,5 S*
18,6	.732	Pg 11	-	-		RD 18,6 S
19,1	.750	-	-	-		RD 19,1 S*
20,4	.803	Pg 13,5	ISO-20	-		RD 20,4 S
20,6	.812	-	-	-		RD 20,6 S*
22,5	.885	Pg 16	-	1/2"		RD 22,5 S
23,8	.937	-	-	-		RD 23,8 S*
25,4	1.000	-	ISO-25	-		RD 25,4 S*
27,0	1.063	-	-	-	RD 27 S*	
28,3	1.115	Pg 21	-	3/4"	RD 28,3 S	
28,6	1.125	-	-	-	RD 28,6 S*	
30,5	1.210	-	-	-	RD 30,5 S*	
31,8	1.250	-	-	-	RD 31,8 S*	
32,5	1.280	-	ISO-32	-	RD 32,5 S*	
34,6	1.357	-	-	1"	RD 34,6 S*	
34,9	1.375	-	-	-	RD 34,9 S*	
37,0	1.457	Pg 29	-	-	RD 37 S	
38,1	1.500	-	-	-	RD 38,1 S*	
40,5	1.594	-	ISO-40	-	RD 40,5 S*	
41,3	1.625	-	-	-	RD 41,3 S*	
43,2	1.699	-	-	1-1/4"	RD 43,2 S*	
44,5	1.750	-	-	-	RD 44,5 S*	
47,0	1.850	Pg 36	-	-	RD 47 S	

*available upon request



Lightweight and easy to operate tool, designed for punching holes up to 47 mm diameter in the side wall of trunking without the need for pre drilling.

Max centre of hole to edge of trunking: 52 mm

Length : 247 mm
Width : 224 mm
Thickness : 66 mm
Weight: 2,78 kg

