CROATIAN

KOMPRESIJSKA ODCJEPNA STEZALJKA

Kompresijska odcjepna stezaljka koristi se za izvođenje odcjepa sa NN izoliranih vodiča u snopu ovalnim prešanjem. Potrebno je skinuti izolaciju na glavnom i odcjepnom vodiču. Tijelo stezaljke je izrađeno od Al legure otporne na koroziju. Dodatni toploskupljajući izolacijski plašt služi za osiguranje vodonepropusnosti spoja a napravljen je od UV otpornog polimera. Stezaljka nije predviđena za montažu pod naponom.

Tip: ALOKS

Materijal: Al. legura, DIN 1725

Standard: EN 61238-1

ENGLISH

Compression Branch Clamp

The compression branch clamp is designed for tapping insulated low-voltage bundled conductors using oval crimping. Insulation must be removed from both the main and branch conductors. The clamp body is made from corrosion-resistant aluminum alloy. An additional heat-shrink insulating sleeve ensures a watertight connection and is made from UV-resistant polymer. This clamp is not suitable for live installation.

Type: ALOKS

Material: Al. alloy, DIN 1725

Standard: EN 61238-1







Tehnički Podaci | Technical Data

TIP Type	Presjek vodiča (mm2) Cross-section Conductor (mm2)		Dimenzije (mm) Dimensions (mm)					Broj prešanja Number Crimps
	Glavni Main	Odcjepni Branch	b	h	d	D	L	
ALOKS 16-6	16	6	17.5	23.5	3.2	5.6	25	2
ALOKS 16-10	16	10	17.5	23.5	4.5	5.6	25	2
ALOKS 16-16	16	16	17.5	23.5	5.6	5.6	25	2
ALOKS 25-6	25	6	17.5	23.5	3.2	6.8	25	2
ALOKS 25-10	25	10	17.5	23.5	4.5	6.8	25	2
ALOKS 25-16	25	16	17.5	23.5	5.6	6.8	25	2
ALOKS 25-25	25	25	17.5	23.5	6.8	6.8	35	3
ALOKS 35-6	35	6	17.5	23.5	3.2	8.0	25	2
ALOKS 35-10	35	10	17.5	23.5	4.5	8.0	25	2
ALOKS 35-16	35	16	17.5	23.5	5.6	8.0	25	2
ALOKS 35-25	35	25	17.5	23.5	6.8	8.0	35	3
ALOKS 35-35	35	35	17.5	23.5	8.0	8.0	35	3
ALOKS 50-6	50	6	23.0	31	3.2	10.0	25	2
ALOKS 50-10	50	10	23.0	31	4.5	10.0	25	2
ALOKS 50-16	50	16	23.0	31	5.6	10.0	25	2
ALOKS 50-25	50	25	23.0	31	6.8	10.0	35	3
ALOKS 50-35	50	35	23.0	31	8.0	10.0	35	3
ALOKS 50-50	50	50	23.0	31	10.0	10.0	50	4
ALOKS 70-6	70	6	25.5	34	3.2	11.5	25	2
ALOKS 70-10	70	10	25.5	34	4.5	11.5	25	2
ALOKS 70-16	70	16	25.5	34	5.6	11.5	25	2
ALOKS 70-25	70	25	25.5	34	6.8	11.5	35	3
ALOKS 70-35	70	35	25.5	34	8.0	11.5	35	3
ALOKS 70-50	70	50	25.5	34	10.0	11.5	50	4
ALOKS 70-70	70	70	25.5	34	11.5	11.5	50	4